

TeakSphere: A revolutionary approach to resin flooring, the TeakSphere system imitates the finish of wood with the waterproof and elastic qualities of resin, allowing for an environmentally sensible alternative to real teak floors.

APPLICATION TIME: 10 DAYS (typical)
A bespoke hand-applied finish throughout

GUARANTEE: 15 YEARS
An extended warranty reflects the system's longevity

THICKNESS: 8-9 MM
A bespoke build up with greater depth

AN INNOVATIVE SOLUTION

- Completely waterproof and impervious
- Resistant to warping or buckling
- Based on plant oil biopolymer
 - Exceptional durability
 - Fully waterproof
- No teak trees destroyed
- Almost any colour possible

TYPICAL DATA

| | |
|---------------------|---------------------------------|
| Layers | 6 |
| Elasticity | 170% |
| Shore Hardness | D50 |
| Abrasion Resistance | Excellent |
| Fire Classification | B _{fl} s1 - EN 13501-1 |

| | |
|-----------------------------|------------------|
| Area Use Classification | 23/33/42 - EN685 |
| Impact Sound Reduction | 4dB+ |
| Slip Rating | R10 EN 51130 |
| Resistance to Chair Castors | Good |
| FeRFA Type | Type 8 - BS 8204 |

